

Collared Eyebolts - Quality Range

UNC thread

- Material:** BS970-080A27 hardened and tempered
Safety Factor: MBL equals 5 x SWL
Standard: BS4278 - table 4 - 1984
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material
Note: Electro galvanised (zinc plated) also available - prices on request

| safe working load | diameter thread | diameter base | diameter eye outside | diameter eye inside | thickness collar | height | thread length | product code | weight each |
|-------------------|-----------------|---------------|----------------------|---------------------|------------------|---------|---------------|--------------|-------------|
| tonnes | a inch | b mm | c mm | e mm | f mm | g mm | h mm | | kg |
| * 0.10 | 1/4 | 22 | 33 | 15 | 7 | 36 | 18 | 20201 | 0.06 |
| * 0.15 | 5/16 | 22 | 33 | 15 | 7 | 36 | 18 | 20202 | 0.06 |
| 0.25 | 3/8 | 22 | 33 | 15 | 7 | 36 | 18 | 20203V | 0.06 |
| 0.50 | 1/2 | 29 | 44 | 20 | 10 | 48 | 23 | 20205V | 0.15 |
| 0.90 | 5/8 | 36 | 52 | 24 | 12 | 58 | 28 | 20207V | 0.27 |
| 1.40 | 3/4 | 45 | 66 | 30 | 14 | 73 | 35 | 20208V | 0.54 |
| 2.00 | 7/8 | 52 | 77 | 35 | 17 | 84 | 40 | 20209V | 0.85 |
| 2.75 | 1 | 58 | 85 | 39 | 20 | 94 | 46 | 20210V | 1.13 |
| 3.50 | 1.1/8 | 65 | 96 | 44 | 22 | 106 | 51 | 20211V | 1.62 |
| 4.50 | 1.1/4 | 72 | 106 | 48 | 24 | 117 | 56 | 20212V | 2.37 |
| * 6.50 | 1.1/2 | 81 | 118 | 54 | 27 | 131 | 63 | 20214V | 3.12 |
| 9.00 | 1.3/4 | 101 | 148 | 68 | 34 | 164 | 79 | 20216 | 6.27 |
| 12.00 | 2 | 115 | 168 | 76 | 38 | 186 | 89 | 20218 | 9.58 |

sizes marked * are additional and proportional to the specification

